

## CABLE SPLICE ENCLOSURE AND COMPONENTS

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of priority to U.S. Provisional Application  
5 Serial Number 60/291,953, entitled "Optical Fiber Enclosure Useful to Provide Voice  
and Data Services," filed May 21, 2001. This application is related to U.S.  
Provisional Application Serial Number 60/237,894, entitled "Systems to Provide  
Video, Voice and Data Services Via Fiber Optic Cable," filed October 4, 2000; U.S.  
Provisional Application Serial Number 60/244,052, entitled "Systems to Provide  
10 Video, Voice and Data Services Via Fiber Optic Cable - Part 2," filed October 26,  
2000; U.S. Provisional Application Serial Number 60/258,837, entitled "Systems to  
Provide Video, Voice and Data Services Via Fiber Optic Cable - Part 3," filed  
December 28, 2000; U.S. Non-Provisional Application Serial No. 09/899,410, entitled  
"System and Method for Communicating Optical Signals Between a Data Service  
15 Provider and Subscribers," filed July 5, 2001; and U.S. Non-Provisional Application  
Serial No. 09/971,363, entitled "System and Method of Communicating Optical  
Signals Upstream and Downstream Between a Data Service Provider and  
Subscribers," filed October 4, 2001. The disclosure of the priority document and each  
of the related documents is hereby fully incorporated by reference.

20

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to video, voice, and data communications. More  
particularly, the present invention relates to an enclosure for facilitating and  
25 protecting splices and connections in communication networks.

## 2. Description of the Related Art

When communication services are provided to homes and businesses, many cable splices and connections are needed between the provider and the subscriber. In a typical communication distribution system, a distribution cable can carry communication signals to and from the provider. Individual subscriber drop lines can be spliced from the distribution cable to provide the communication services to each individual subscriber. Where such splices or connections are made, an enclosure is typically used to protect these structures from physical damage and environmental elements, such as moisture, dirt, etc.

10       The distribution cable and the drop lines are transmission mediums for the communication services. Such transmission mediums can comprise optical waveguides, coaxial cables, telephone cables, electrical wires, and other like waveguides or devices. As used throughout this specification, the term "optical waveguide" denotes an optical fiber, a planar light guide circuit, a fiber optic pigtail, and other optical waveguides. A typical distribution cable can comprise one or more individual transmission mediums bundled together. Each individual transmission medium of the distribution cable can provide services to a limited number of subscribers. Typically, each individual transmission medium of the distribution cable is spliced or connected to one or more individual drop lines.

20       Conventional enclosures can protect the splices or connections of the transmission mediums in the communication distribution system. Such enclosures can have a first port, which allows a first portion of the distribution cable and drop lines to enter the enclosure. Additionally, conventional enclosures can have a second port, which allows a second portion of the distribution cable and drop lines to enter the enclosure. Inside the enclosure, an individual transmission medium of the

25

Another problem of conventional enclosures can be associated with the strain relief device, which holds individual drop lines in the enclosure. A conventional strain relief device 700 is illustrated in Figures 7A and 7B. Strain relief device 700 typically comprises a support member 702. Support member 702 can be attached to a conventional enclosure (not shown). Support member 702 can have notches 704 for receiving a clamp 708 after clamp 708 is tightened. Clamp 708 can attach an individual drop line 706 to support member 702. However, notches 704 typically do not hold clamp 708 in place before clamp 708 is tightened. Clamp 708 can fit loosely around support member 702 before it is tightened. But, clamp 708 can easily fall off of support member 702 until it is tightened around drop line 706 and support member 702. Such a configuration can be troublesome since drop line 706 and clamp 708 need to be held in place while clamping them to support member 702. Additionally, clamp 708 usually cannot be pre-installed on support member 702 at the factory, because notches 704 will not retain clamp 708.

There is a need in the art, therefore, for an improved enclosure that allows individual drop lines to be added to, or removed from, the enclosure without disturbing existing transmission mediums or splices contained therein. There is also a need in the art for an improved enclosure that secures and protects the gasket between the cover plate and the enclosure's housing when the cover plate is removed. Additionally, a need exists in the art for an improved strain relief device that allows a clamp to be installed at the factory, as well as in the field.

#### SUMMARY OF THE INVENTION

The present invention is generally drawn to a device useful in providing communications services to homes and businesses. More specifically, the present

invention is directed to an enclosure that can facilitate and protect splices and connections between a distribution cable and an individual subscriber drop line. The enclosure can facilitate connections between the distribution cable and the drop line by providing separate ports for the distribution cable and the drop line. Additionally,  
5 the enclosure can facilitate multiple connections between the distribution cable and multiple drop lines by providing separate ports for each drop line.

The enclosure can have a first port, a second port, and one or more drop ports. A first portion of the distribution cable can enter the enclosure through the first port, and a second portion of the distribution cable can enter the enclosure through the  
10 second port. One or more drop lines can enter the enclosure through a respective drop port. Inside the enclosure, an individual transmission medium can be separated from the distribution cable and spliced to form one or more drop lines. The individual drop ports can allow additional drop lines to be added or removed without disturbing items existing in the enclosure. Items existing in the enclosure can include the distribution  
15 cable, the transmission medium from the distribution cable, other drop lines, and splices or connections.

The present invention can allow multiple openings for drop lines in the enclosure without compromising the ability of the enclosure to keep out moisture and dirt. Each drop port can have a removable drop plug that can prevent moisture and  
20 dirt from entering the enclosure. If the drop port is empty, then a closed drop plug can substantially seal the empty drop port opening. If the drop port contains a drop line, then an open drop plug can substantially seal the drop port opening around the drop line. If necessary, a sealant device such as tape, caulk, insulation, or other similar items can be provided around the drop line to further seal the drop port  
25 opening.

The present invention can also allow access to the interior of the enclosure without compromising the ability of the enclosure to keep out moisture. A removable cover plate having a sealing member such as a gasket can be attached to the enclosure. The sealing member can be coupled to the cover plate. Alternatively, the sealing member can be coupled to the enclosure's housing. The sealing member can be protected from damage and dirt by remaining coupled to the cover plate or housing when the cover plate is removed. This configuration can also prevent the separate tasks of removing and protecting the sealing member when the cover plate is removed. Additionally, the sealing member can seal any gaps between the cover plate and the removable drop plugs in the drop ports.

The present invention can also provide strain relief for the drop lines or distribution cable that enter the enclosure. A strain relief device according to the present invention can comprise a support member and a clamping device. The support member can be attached to the enclosure. The clamping device can be coupled to the support member. The clamping device can then attach the drop line or the distribution cable to the support member, thereby relieving the strain on the drop line or the distribution cable. The support member can have holes or slots for receiving the clamping device. The clamping device can fit into the holes or slots. The holes or slots can mechanically hold the clamping device in place, thereby allowing the clamping device to be pre-installed at the factory or in the field.

A splitting device for dividing signals among a plurality of subscribers can also be provided in the enclosure of the present invention. If the distribution cable contains optical waveguides, then the splitting device can be an optical splitter. The optical splitter can divide optical signals among a plurality of subscribers.

These and other aspects, objects, and features of the present invention will become apparent from the following detailed description of the exemplary embodiments, read in conjunction with, and reference to, the accompanying drawings.

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a functional block diagram illustrating some core components of an exemplary operational environment for an enclosure according to the present invention.

Figure 2A illustrates a pedestal-mount configuration of an enclosure according to one exemplary embodiment of the present invention.

Figure 2B illustrates a strand-mount configuration of an enclosure according to another exemplary embodiment of the present invention.

Figure 3 illustrates a cross section of an enclosure according to an exemplary embodiment of the present invention.

Figure 4A illustrates a perspective view of an enclosure according to an exemplary embodiment of the present invention.

Figure 4B illustrates a cross section of a cover plate having a sealing member retaining device according to an exemplary embodiment of the present invention.

Figure 5 illustrates a perspective view of a strain relief device according to an exemplary embodiment of the present invention.

Figures 6A, 6B, 6C, and 6D illustrate alternative support members of a strain relief device according to exemplary embodiments of the present invention.

Figures 7A and 7B illustrate a conventional strain relief device.

## DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings, in which like reference numerals represent like elements.

5           The present invention is directed to an enclosure that can facilitate and protect splices and connections between a distribution cable and an individual subscriber drop line. An enclosure according to the present invention can provide separate ports for the distribution cable and the drop line. The separate ports can allow additional drop lines to be added or removed without disturbing the distribution cable, existing drop  
10 lines, or other existing items in the enclosure. The enclosure according to the present invention can also contain a splitting device such as an optical splitter for dividing signals among a plurality of subscribers. The present invention can also provide a gasket coupled to the enclosure or to a cover plate on the enclosure. Accordingly, the gasket remains protected even when the cover plate is removed. A strain relief device  
15 according to the present invention can allow a clamp to be pre-installed on the device during manufacturing or in the field. The strain relief device according to the present invention can mechanically hold the clamp in place until it is tightened.

Figure 1 is a functional block diagram illustrating some core components of an exemplary operational environment **100** for an enclosure according to the present  
20 invention. Exemplary operational environment **100** can comprise a data service headend or hub **110** connected to a processing node **120** of an optical network. Processing node **120**, in turn, can be connected to optical taps **130a**, **130b**, **130c** (collectively "optical taps **130**"). Optical taps **130** can be connected to a plurality of subscriber optical interfaces **140**, which can each be connected to an individual  
25 subscriber **142**. Subscribers **142** can comprise individual home subscribers or

business subscribers. Optical taps 130 can be provided in an enclosure 200 according to the present invention. Enclosure 200 will be discussed in detail below with reference to Figures 2, 3, 4A, and 4B.

Respective components of exemplary operational environment 100 are  
5 connected by trunk lines 160, 170, and 180, a distribution cable 150, and drop lines 155. Trunk lines 160, 170, and 180, distribution cable 150, and drop lines 155 can each comprise a transmission medium. Distribution cable 150 can comprise a plurality of individual transmission mediums 152. Alternatively, distribution cable 150 can comprise a single transmission medium 152. Distribution cable 150,  
10 individual transmission medium(s) 152, drop lines 155, and trunk lines 160, 170, and 180 can each comprise an optical waveguide(s).

While only an individual processing node 120, three optical taps 130 (130a, 130b, and 130c), and an individual subscriber optical interface 140 are fully illustrated in Figure 1, a plurality of processing nodes 120, optical taps 130, and  
15 subscriber optical interfaces 140 can be employed. Typically, multiple processing nodes 120 can be connected to hub 110, multiple optical taps 130 can be connected to each distribution cable 150, and multiple subscriber optical interfaces 140 can be connected to each optical tap 130.

Distribution cable 150 and trunk lines 160, 170, and 180 are represented by  
20 arrows, where the arrowheads illustrate exemplary directions of data flow between respective components. As shown in Figure 1, trunk lines 160, 170, and 180 can propagate optical signals from hub 110 to processing node 120. First trunk line 160 can carry broadcast video and other signals. The signals can be transmitted in a traditional cable television format wherein the broadcast signals are modulated onto  
25 carriers, which in turn modulate an optical transmitter (not shown) in hub 110.



Second trunk line **170** can carry downstream targeted services such as data and telephone services to be delivered to one or more subscriber optical interfaces **140**. In addition to carrying subscriber-specific optical signals, second trunk line **170** can also propagate internet protocol broadcast packets, as is understood by those skilled in the art.

Third trunk line **180** can also be provided to transport data signals upstream from processing node **120** to hub **110**. The optical signals propagated along third trunk line **180** can also comprise data and telephone services received from one or more subscribers. Similarly to second trunk line **170**, third trunk line **180** can also carry IP broadcast packets, as is understood by those skilled in the art.

Third trunk line **180** is illustrated with dashed lines to indicate that it is optional. As illustrated by the double arrows, second trunk line **170** can propagate optical signals in both the upstream and downstream directions. In such an exemplary configuration where second trunk line **170** propagates bi-directional optical signals, only two trunk lines **160**, **170** would be needed to support the optical signals propagating between hub **110** and processing node **120**. In another exemplary configuration (not shown), a single trunk line can be the only link between hub **110** and processing node **120**. In such a single trunk line configuration, three different wavelengths can be used for the upstream and downstream signals. Alternatively, bi-directional data can be modulated on one wavelength.

Optical taps **130a**, **130b**, **130c** can comprise splitting devices **132**, **134**, **136**, respectfully. Splitting devices **132**, **134**, **136** can be optical splitters. Optical taps **130** allow multiple subscriber optical interfaces **140** to be coupled to an individual transmission medium **152** of distribution cable **150**. In the exemplary operational environment **100** shown in Figure 1, each individual transmission medium **152** can

provide service to eight subscribers **142**. Those skilled in the art will appreciate that the number of subscriber optical interfaces **140** assigned to a particular individual transmission medium **152** can be varied or changed without departing from the scope and spirit of the present invention.

5           As shown in Figure 1, optical tap **130a** can comprise splitting device **132**, which can be an 8-way optical splitter. The 8-way optical splitter can divide downstream optical signals eight ways to serve eight different subscriber optical interfaces **140**. In the upstream direction, splitting device **132** of optical tap **130a** can combine optical signals received from the eight subscriber optical interfaces **140**. At  
10       optical tap **130a**, a first individual transmission medium **152** is routed from distribution cable **150** to splitting device **132**. First individual transmission medium **152** is then terminated at splitting device **132** to serve eight subscribers.

Optical tap **130b** can comprise splitting device **134**, which can be a 4-way optical splitter serving four subscriber optical interfaces **140**. As shown in Figure 1,  
15       splitting device **134** can be a 4-way optical splitter that is also a pass-through tap. The pass-through tap can extract a portion of the optical signal received at optical tap **130b** to serve the 4-way optical splitter contained therein, while the remaining optical energy can be further propagated downstream to another optical tap **130c** or another subscriber optical interface **140** (not shown). In this exemplary configuration, a first  
20       portion of individual transmission medium **152** can be routed to the 4-way, pass-through splitter (splitting device **134**) in optical tap **130b**. Then, a second portion **152a** of individual transmission medium **152** can be routed from splitting device **134** back into distribution cable **150** and to the 4-way splitter (splitting device **136**) contained in optical tap **130c**.

25           The present invention is not limited to optical taps having 4-way and 8-way

optical splitters. Other optical taps having more or less than 4-way or 8-way splits are within the scope of the present invention.

Other exemplary operational environments for an enclosure according to the present invention are described in U.S. Application Serial No. 09/899,410, entitled  
5 "System and Method for Communicating Optical Signals Between a Data Service Provider and Subscribers," filed July 5, 2001. The present invention is not limited to the exemplary operational environments disclosed in that application or discussed above with reference to Figure 1. The present invention can be applied to any system in which two transmission mediums are coupled together. For example, distribution  
10 cable **150** can comprise coaxial cable(s), telephone wires, or electrical wires. Additionally, distribution cable **150** can comprise any combination of coaxial cable, telephone wires, electrical wires, and/or optical waveguides. Drop lines **155** can then be composed of a suitable transmission medium depending on the application. Drop lines **155** can also comprise any combination of the transmission mediums mentioned  
15 above. Additionally, each component of the system can then be a suitable component to operate with the particular application.

An enclosure **200** according to the present invention will now be described with reference to Figures 2, 3, 4A, and 4B. Enclosure **200** will be described for use with an optical network as described above with reference to Figure 1. However,  
20 enclosure **200** can be used for any of the transmission media discussed above.

Referring now to Figure 2A, a pedestal-mount configuration of enclosure **200** according to an exemplary embodiment of the present invention will be described. Enclosure **200** can protect optical tap **130**, which is represented in Figure 2 by a splitting device **207**. Enclosure **200** comprises a housing **204**. Housing **204** can  
25 comprise first, second, and third ports **P1**, **P2**, **P3** and drop ports **P4-P11**. Enclosure

Drop lines 155 enter enclosure 200 through drop ports P4-P11. For illustrative purposes, the drop line 155 at drop port P4 is shown as originating from splice tray 206 and splitting device 207. Each drop line 155 receives a portion of the signal on transmission medium 152 by way of splitting device 207. Each drop line

5 155 can also be connected to an optical interface 140 to provide service to an individual subscriber 142 (Figure 1). As shown in Figure 2A, eight drop ports P4-P11 and eight drop lines 155 can be provided. However, the present invention is not limited to such a configuration. For example, additional or fewer drop ports than are illustrated in Figure 2A can be provided. Further, more or less drop lines than are

10 illustrated in Figure 2A can be provided. Each drop port does not require a drop line 155. In other words, some drop ports can remain empty. Additionally, splitting device 207 is shown in Figure 2A as a 4-way splitting device. As discussed above, the present invention is not limited to 4-way power division.

Enclosure 200 provides protection for the optical components contained

15 therein. Enclosure 200 can contain optical splitter 207, typically in splice tray 206, as well as space for managing distribution cable 150, individual transmission medium 152, drop lines 155, and any other splices or connectors contained therein. As discussed above, enclosure 200 can be used for any type or combination of transmission mediums. For example, enclosure 200 can be used for optical

20 waveguides. Additionally, enclosure 200 can be used for coaxial cable, telephone cable or wires, and/or electrical wires in place of, or in addition to, optical waveguides.

Referring to Figure 2B, a strand-mount configuration of enclosure 200 according to another exemplary embodiment of the present invention will be

25 described. As shown in Figure 2B, one or more strand clamps 212 can be coupled to

enclosure **200** so that enclosure **200** can be attached to a support cable or wire **210** by strand clamps **212**. Typically, support cable **210** can comprise a steel cable connected between two utility poles. Support cable **210** can provide support for transmission mediums attached thereto. Fiber optic, telephone, electrical, and coaxial cables can be attached to support cable **210**. In the strand-mount configuration, a first portion of distribution cable **150** can enter enclosure **200** through first port **P1**. A second portion of distribution cable **150** can enter enclosure **200** through third port **P3**. Second port **P2** is typically not used in the strand-mount configuration. The unused port **P2** can be sealed to prevent moisture from entering enclosure **200**. All other aspects of enclosure **200** shown in Figure 2B are the same as those shown in Figure 2A.

Referring now to Figures 3, 4A, and 4B, enclosure **200** will be described in more detail. Figure 3 illustrates a cross section of enclosure **200** according to an exemplary embodiment of the present invention. As discussed earlier, enclosure **200** comprises housing **204**. Housing **204** can be made from a variety of materials such as metal or molded plastic. Housing **204** can comprise first, second, and third ports **P1**, **P2**, and **P3**, which allow for entry of distribution cable **150**. Typically, first and second ports **P1** and **P2** are used in a pedestal-mount configuration, while first and third ports **P1** and **P3** are used in a strand-mount configuration. However, any combination or order of ports **P1-P3** can be used without departing from the scope of the present invention. Additionally, fewer or additional ports can be provided in enclosure **200** without departing from the scope of the present invention.

As shown in Figure 3, strand clamps **212** can comprise a support member **212a**, a clamping member **212b**, and a locking member **212c**. Locking member **212c** can comprise a screw or a bolt.

Distribution cable **150** is shown entering enclosure **200** through port **P1**. Once

secured around strength members 307 by tightening locking member 306c, thereby holding strength members 307 to support member 306a.

For a single stage strain relief of distribution cable 150, either hose clamp 304 or strength member clamp 306 can be provided alone for each of ports P1-P3 in housing 204. Alternatively, hose clamp 304 and strength member clamp 306 can both be provided for each of ports P1-P3 in housing 204 to create a two-stage strain relief system for distribution cable 150.

Housing 204 can also comprise drop ports P4-P11. Drop ports P4-P11 can allow drop lines 155 to enter enclosure 200. Inside enclosure 200, drop lines 155 can be routed to a cable or fiber management apparatus such as splice tray 206. Drop ports P4-P11 can be smaller in size than ports P1-P3. In other words, the cross-sectional area of an opening in housing 204 provided by a drop port P4-P11 can be smaller than the cross-sectional area of an opening in housing 204 provided by a port P1-P3. Drop ports P4-P11 can be sized smaller than ports P1-P3 because drop lines 155 are typically comprised of only one or two transmission mediums, while distribution cable 150 is typically comprised of one larger transmission medium or a plurality of transmission mediums.

A strain relief device 308 can be provided at each drop port P4-P11. Strain relief device 308 can be coupled to housing 204 with bolts or screws, or by gluing, welding, or other methods. Strain relief device 308 can be coupled to housing 204. The strain relief device 308 can clamp individual drop lines 155 securely to enclosure 200, thereby relieving strain on drop lines 155. Strain relief device 308 can be provided alone for each of ports P4-P11 in housing 204 to create a single stage strain relief of drop lines 155. Strain relief device 308 can be sized to correspond to the size of the drop line 155 that enters a respective one of drop ports P4-P11. Accordingly,

strain relief device **308**, which accommodates the drop line **155**, can be smaller than hose clamp **304**, which accommodates distribution cable **150**. In other words, hose clamp **304** can define a first hole through which a distribution cable **150** can be inserted, and strain relief device **308** can define a second hole through which a drop line **155** can be inserted. Consequently, a cross-sectional area of the second hole can be smaller than a cross-sectional area of the first hole. Strain relief device **308** will be discussed in more detail below with reference to Figures 5 and 6A-6D.

Drop ports **P4-P11** allow easy access for adding or removing drop lines **155** from enclosure **200**. Additionally, drop ports **P4-P11** make it possible to add and remove drop lines **155** without disturbing other drop lines **155**, distribution cable **150**, or individual transmission medium **152**. This feature is especially useful when drop lines **155** comprise one or more optical fiber strands. The present invention facilitates easy addition or removal of drop lines **155** whether enclosure **200** is mounted in a pedestal-mount or strand-mount configuration. Each of drop ports **P4-P11** can be sized to allow a drop line **155** having one or more optical fiber strands to be inserted. Such optical fiber strand(s) of drop line **155** can provide service to subscribers **142** (Figure 1). Additionally, drop line **155** can comprise one or more layers of protective insulation to strengthen drop line **155** and to protect the optical fiber strand(s) contained therein.

Typically, drop lines **155** comprise a single fiber strand surrounded by a protective sleeve. In some cases, drop lines **155** may also comprise a coaxial cable (not shown) for delivery of RF modulated signals, and/or it may comprise other individual transmission mediums (not shown) such as telephone or electrical wires. The other transmission mediums can be used for a variety of purposes. For example, the other transmission mediums can provide power from a network to feed electronic

circuitry at the subscriber's location, or it can carry telephone calls or data. Additionally, drop lines **155** can comprise a messenger, which is a strength member (not shown).

Splice tray **206** is a management area for enclosing splices and connections.

5 The splices and connections can be between drop line **155** and individual transmission medium **152** of distribution cable **150**. Splice tray **206** can also enclose an electrical interface (not shown) for any of the transmission mediums discussed above. Additionally, at least one splitting device **207** can be provided in splice tray **206**. Splitting device **207** can comprise an optical splitter and can provide either 4-way or  
10 8-way optical power division. Alternatively, splitting device **207** can provide 4-way power division preceded by 2-way power division in the case of a 4-way pass-through tap. The present invention is not limited to the power divisions described above. Other types of splitting can be used. For example, more or less than 4-way or 8-way splits can be used.

15 A second cable or fiber management apparatus such as a second splice tray **206a** can also be provided in enclosure **200**. When second splice tray **206a** is provided, a two-stage operation of coupling drop lines **155** to transmission medium **152** can be performed. In splice tray **206**, transmission medium **152** can be coupled to splitting device **207**. If splitting device **207** provides 8-way power division, then each  
20 of eight connector transmission mediums (not shown) can be coupled on one end to splitting device **207**. The other end of each connector transmission medium can be routed to second splice tray **206a**. In second splice tray **206a**, drop lines **155** can be coupled as needed to a respective connector transmission medium. If splitting device **207** provides more or less than 8-way power division, then the number of connector  
25 transmission mediums can be adjusted accordingly.



Referring to Figure 4A, further features of enclosure **200** will be described. Figure 4A illustrates a perspective view of enclosure **200** according to an exemplary embodiment of the present invention. As shown in Figure 4A, drop ports **P4-P11** can comprise slots or channels in housing **204** of enclosure **200**. Drop plugs **406** and **408** can be provided to substantially seal drop ports **P4-P11** to prevent moisture from entering enclosure **200**. Drop plugs **406**, **408** can be composed of cast metal, molded plastic, or other materials similar to the materials of housing **204**. Additionally, a sealing means (not shown) formed of rubber or a similar material can be provided with drop plugs **406**, **408** to further seal drop ports **P4-P11**.

As illustrated, drop lines **155** can be provided in drop ports **P10** and **P11**. For those drop ports where a drop line **155** is provided, an open drop plug **406** can be used to substantially seal drop ports **P10** and **P11** around drop lines **155**. Open drop plugs **406** have a concave-rounded end **406a** that substantially seals around drop lines **155**. If necessary, additional sealing devices **410** may be provided around drop lines **155** to further seal any remaining opening(s) in drop ports **P10** and **P11**. Sealing devices **410** can comprise sealant tape, caulk, insulation, washers, or other similar materials. In an alternative embodiment (not shown), open drop plug **406** can comprise a grommet-type of plug, where a drop line **155** can be inserted into a hole in the grommet-type plug.

In the exemplary embodiment illustrated in Figure 4A, ports **P4-P9** do not contain a drop line **155**. For each empty drop port **P4-P9**, a closed drop plug **408** can be provided. Closed drop plugs **408** can be shaped to substantially fill the slot of empty drop ports **P4-P9**. As shown, closed drop plugs **408** can comprise a convex-rounded end **408b** for that purpose.

The present invention is not limited to the number or shape of drop ports and

drop plugs shown in Figure 4A. For example, additional or fewer drop ports than those illustrated in Figure 4A can be provided. If enclosure 200 is provided in a dry location, drop plugs 406 and 408 can be omitted. Additionally, drop ports P4-P11 can have a different shape than that shown in Figure 4A, or drop ports P4-P11 can be  
5 holes in enclosure 204. In those alternative configurations, drop plugs 406 and 408 can be shaped as required to correspond to the shape of drop ports P4-P11.

Figure 4A also illustrates a cover plate 402 for enclosing an interior of housing 204. As shown, cover plate 402 can be removably coupled to housing 204. Alternatively, cover plate 402 can be pivotally coupled to housing 204 by a hinge (not  
10 shown) that is coupled to both cover plate 402 and housing 204. Cover plate 402 can be coupled to housing 204 at an exterior edge 405 of housing 204. Additionally, cover plate 402 can rest on an exterior edge 408a of each drop plug 406 and 408. A sealing member 404 can be provided to substantially seal any gaps between cover plate 402 and housing 204 and between cover plate 402 and exterior edges 408a of  
15 drop plugs 406, 408 to prevent moisture from entering enclosure 200. Sealing member 404 can comprise a gasket.

As shown, sealing member 404 can be coupled to the perimeter of cover plate 402. In such an exemplary configuration, when cover plate 402 is removed from housing 204, sealing member 404 can be removed with cover plate 402 so that sealing  
20 member 404 does not have to be separately removed and replaced. Accordingly, such a configuration provides convenience for simplified removal of both cover plate 402 and sealing member 404. Additionally, sealing member 404 remains protected by cover plate 402 while they are removed from housing 204.

Sealing member 404 can be coupled to cover plate 402 in a variety of ways.  
25 For example, sealing member 404 can be coupled to cover plate 402 with an adhesive

The adhesive can be an RTV adhesive. Additionally, a sealing member retaining device **403** (Figure 4B) can be molded on, or coupled to, the perimeter of cover plate **402**. Figure 4B illustrates a cross section of retaining device **403** on cover plate **402** according to an exemplary embodiment of the present invention. Retaining device **403** can comprise a channel molded in the perimeter of cover plate **402**. Retaining device **403** can then hold sealing member **404** to cover plate **402** by tension or compression. Alternatively, individual holders such as clips (not shown) can be provided on the perimeter of cover plate **402** to hold sealing member **404** in place. Furthermore, sealing member **404** can be coupled to exterior edge **405** of housing **204**. Any of the methods discussed above for coupling sealing member **404** to cover plate **402** can be used to couple sealing member **404** to housing **204**.

Referring to Figures 5 and 6A-6D, strain relief device **308** for drop lines **155** will be described in detail. Figure 5 illustrates a perspective view of strain relief device **308** according to an exemplary embodiment of the present invention. Strain relief device **308** can comprise a support member **308a** having a clamp receiving portion **308b**. A clamping device **308c** can be coupled to support member **308a** at clamp receiving portion **308b**. During operation, a drop line **155** can be inserted into clamping device **308c**. Clamping device **308c** can then closed around drop line **155** to secure drop line **155** to support member **308a**.

Clamping device **308c** can be any suitable device for clamping drop line **155**. For example, clamping device **308c** can comprise a band that is fastened back on itself to secure drop line **155** to support member **308a**. Such a band can comprise a first portion and a second portion, wherein the first portion of the band fastens to the second portion of the band. In an exemplary embodiment, a plastic band having the structure described above can be used. Such a plastic band is known by the trade

name TYWRAP. Alternatively, clamping device **308c** can comprise a hose clamp.

Referring to Figures 6A-6D, a support member for a strain relief device according to alternative exemplary embodiments of the present invention will be described. In Figure 6A, a support member **602** can comprise one or more clamp receiving portions **604**. Clamp receiving portions **604** can be holes in support member **602**. A clamping device can be threaded through the holes of clamp receiving portion **604**. As shown in Figure 6C, support member **602** can comprise a plurality of clamp receiving portions **604** for receiving a plurality of clamping devices. Accordingly, a strain relief device **308** comprising the support member **602** of Figure 6C can provide strain relief to a plurality of drop lines **155** entering enclosure **204** through a plurality of respective drop ports.

Alternatively, in Figure 6B, a support member **606** can comprise one or more clamp receiving portions **608**. Clamp receiving portions **608** can comprise slots in support member **606**. Each slot can be T-shaped and can comprise a first opening **608a** disposed substantially perpendicular to an edge **606a** of support member **606** and a second opening **608b** leading from the first opening **608a** to edge **606a**. Clamp receiving portions **608** allow for easy installation of a clamping device. A clamping device can be threaded into first openings **608a** of clamp receiving portions **608**. Alternatively, the clamping device can be inserted into first openings **608a** of clamp receiving portions **608** through second openings **608b**. As shown in Figure 6D, support member **606** can comprise a plurality of clamp receiving portions **608** for receiving a plurality of clamping devices. Accordingly, a strain relief device **308** comprising the support member **606** of Figure 6D can provide strain relief to a plurality of drop lines **155** entering enclosure **204** through a plurality of respective drop ports.

The present invention is not limited to clamp receiving portions **604** and **608** shown in Figures 6A-6D. For example, only one clamp receiving portion **604** or **608** can be provided. Also, first opening **608a** can be disposed at other angles that are not substantially perpendicular to edge **606a**. Additionally, other shapes of clamp  
5 receiving portions **604**, **608** can be provided within the scope of the present invention.

The clamp receiving portions of the present invention described above mechanically hold the clamping device in place even before it is tightened against the support member and a transmission medium. Accordingly, the clamp receiving portions described above allow a manufacturer to pre-install a clamping device during  
10 manufacturing of the strain relief device. The clamp receiving portions mechanically hold the clamping device in place until it is used. Thus, the clamping device would not require installation in the field. Additionally, the use of a clamp receiving portion **608** comprising first and second openings allows for quick and easy replacement of a clamping device in the field. The use of a clamp receiving portion **604** comprising a  
15 hole in the support member can also serve that function. The clamp receiving portions described above also mechanically hold the clamping device in place while a transmission medium is inserted and secured to the support member.

Although specific embodiments of the present invention have been described above in detail, it will be understood that this description is merely for purposes of  
20 illustration. Various modifications of the disclosed aspects of the preferred embodiments, in addition to those described above, may be made by those skilled in the art without departing from the spirit of the present invention defined in the following claims, the scope of which is to be accorded the broadest interpretation so as to encompass such modifications and equivalent structures.